

PKS 890 / 880 / 740 series

Self-propelled Aerial Platforms

PKS 890 / 880 / 740 series

PKS890 can be moved in a truck with high roof. Super compact PKS880 and PKS740 can be moved in a truck with low roof.

The hydraulic grader is a very important and suggested accessory to allow the platform to be levelled up to a 20 cm difference in height.

EN 280 CE CERTIFICATED, FOR INTERNAL USE WITHOUT WIND.

TECHNICAL DESCRIPTION

Speed: From 0 to 25 m/mins with movement at height

Controls: Cage supplied with all controls, check control, timer, key, lift/lowering, CCS and ICS safety systems, Electronic control of platform slope with automatic block, Acoustical movement device

Batteries: 2 130Ah 12Vdc batteries with reinforced plates

Battery charger: Portable, 220V, 50Hz, 15A, 24Vdc

Lift: Hydraulic system with motor 2KW, safety valve and emergency lowering system

Steering: Hydraulic system with motor 500W





























Tower: Made of anodised aluminium, telescopic system with BACKLASH RECOVERY, FLEIER transmission chains, PLUNGING hydraulic cylinder, 12 sliding rollers for each tower with VRS

Turning circle: 2.5 metre.

Slope surmountable: With closed machine, frontal 15%, lateral 5%

Traction: 2 500W engines 24Vdc operated by 1 electronic circuit card with MOSFET technology and computerised energy recovery



		PKS 890	PKS 880	PKS 740	PKS 890 Z	PKS 880 Z	PKS 740 Z
	A	1,66 mt	1,45 mt	1,45 mt	1,66 mt	1,45 mt	1,45 mt
		925	990	790	1260	1110	870
	Cod. CM03PKS	H 7,80 mt	H 7,90 mt	H 6,35 mt	H 7,80 mt	H 7,90 mt	H 6,35 mt
		Cestello Fisso <i>Fixed frame</i>					
		 					
		 					
	Cod. C/PICK	H 7,80 mt	H 7,90 mt	H 6,35 mt	H 7,80 mt	H 7,90 mt	H 6,35 mt
		Cestello Piking <i>Piking frame</i>					
		 					
		 					
	Cod. CESTROPKS				H 7,97 mt		H 6,50 mt
		Cestello Rotante <i>Rotating frame</i>					
		 					
		 					
	Cod. C/ESTPKS				H 7,80 mt		H 6,35 mt
		Cestello Estensibile <i>Frame to be extended</i>					
		 					
		 					
	Cod. C/SUPPKS				H 8,90 mt	H 8,80 mt	H 7,33 mt
		Cestello Superiore <i>Superior frame</i>					
		